For information about other American International automotive accessories visit our website at:

http://www.americaninternational.net









### **Automotive Products Division**

1040 Avenida Acaso • Camarillo, CA 93012, U.S.A. USA Sales (800) 336-6500 Canada Sales (888) 922-3006 • USA Fax (805) 388-7950

**CUSTOMER HELP LINE**USA 800-323-4329 • Canada 800-245-8777

## **VEHICLE APPLICATIONS**


(ISO Mount Only)

Mercury 1993-98 VILLAGER Nissan 1993-98 QUEST

iNDK715

# CAUTION: BEFORE PROCEEDING, SET PARKING BRAKE AND DISCONNECT BATTERY GROUND CABLE.





#### 1993-98 NISSAN QUEST / MERCURY VILLAGER

## DASH DISASSEMBLY INSTRUCTIONS

- 1. Remove (1) screw in center top portion of dash trim surrounding A/C,heater, radio and storage box. Unsnap dash trim. (see fig. A)
- 2. Remove (4) screws from the front sides of factory radio. Slide radio forward enough to disconnect power, speakers and antenna. Remove radio.
- 3. To retain use of the factory storage box, cut away equalizer provision as illustrated in fig. B.
- 4. To install an equalizer, leave main bracket intact. Unsnap equalizer trim and break-away support ribs for 1"x 7" standard size equalizer. The trim panel can be cut at the vertical score lines provided on the face of the equalizer trim for small width equalizers or accesories. Mount equalizer using slots in sides of main bracket as shown in fig. C.
- 5. Remove (4) screws surrounding radio storage box assembly in dash cavity. Install radio as per manufacturers instructions and wire. American International wiring harness (#NWH-700) is available separately for your vehicle to simplify wiring. Check with the store where this kit was purchased for availability, or call 1-800-323-4329 to special order.
- 6. Re-install entire kit assembly into cavity by reversing step 5.

